



SOLAR PROTECTION LOUVRES

LOUVRES TYPES

FIXED: regulation 0°, 15°, 30°, 45°
MOVABLES: Motorized and manuals

LOUVRES SIZES

120, 145, 190, 250, 300 and 400 mm
For other sizes please consult Technical Department

CATEGORIES ACHIEVED AT TEST CENTRE

Wind loading resistance (UNE 13659): **Class 6 (Máx.)**

Reference test: Louvres 120 mm: 1.8 m, Louvres 145 mm: 2.2 m, Louvres 190 mm: 2.5 m, Louvres 250 mm: 3.0 m, Louvres 300 mm: 3.5 m, Louvres 400 mm: 4.2 m

EXTRUSION ALLOY

6063 T-5

PROFILE THICKNESS

LOUVRES	THICKNESS
120 mm	1.25 mm
145 mm	1.35 mm
190 mm	1.70 mm
250 mm	1.90 mm
300 mm	2.00 mm
400 mm	2.50 mm

MAXIMUM RECOMMENDED LENGTH*

LOUVRE SIZE	MAXIMUM RECOMMENDED LENGTH*	
	FIXED LOUVRES	MOVABLE LOUVRES
120 mm	1.8 m	
145 mm	2.2 m	1.9 m
190 mm	2.5 m	2.4 m
250 mm	3.0 m	3.0 m
300 mm	3.5 m	3.4 m
400 mm	4.2 m	4.0 m

Depending on project specifications a larger free louvre length will be attainable (Consult)

FINISHES

Colour powder coating
(RAL, mottled & rough)

According to Qualicoat standard >60 microns

Wood effect powder coating

According to Qualideco standard

Anodized

According to Ewwa Euras

Standard Class 15

Optionally Class 20 and 25

