

ENERGY EFFICIENCY

Thermal Transmission Coefficient
 $U_w \geq 1.1$ (W/m²K)

Please consult typology, dimensions and glazing

ACCUSTIC INSULATION

Maximum glazing: **45 mm**

CATEGORIES ACHIEVED AT TEST CENTRE

Protection against atmospheric agents

Air permeability (EN 12207):

Class 4

Water tightness (EN 12208):

Class 9A

Wind resistance (EN 12210):

Class A3

Reference test: 2.700 x 2.530 mm / 3 sashes

Security test: **PAS24**

Passed

Configuration 330. 2701 x 2517 mm / 3 sashes

SECTIONS	Frame 73 mm Sash 73 mm	EXTRUSION ALLOY	6063 T-5
PROFILE THICKNESS	Door 1.8 mm	POLYAMIDE STRIP LENGTH	Polyamide 6.6 reinforced with 25% fiberglass: Frame 20 mm Sash 30 mm
MAXIMUM DIMENSIONS	Width (L) = 1.200 mm Height (H) = 3.000 mm	OPENING POSIBILITIES	Inward: 1 to 14 sashes Outward: 1 to 14 sashes Possibility of corner sash at 90° without mullion
MAXIMUM WEIGHT/SASH	120 Kg	ACCESSIBILITY	Possibility of embedded low threshold
FINISHES	Colour powder coating (RAL, mottled, rough...) According to Qualicoat >60 microns Wood effect powder coating According to Qualideco standard Anodized According to Ewwa Euras Standard Class 15 Optionally Class 20 and 25 Optionally bicoloured		

Please consult regarding maximum weight and dimensions according to types

